







-  your idea...
-  our solutions...
-  your success...



Accessories for Frequency Converters



Connectors

<u>Article</u>	<u>Description</u>	
 4 243	DIN connector	<i>flying DIN, 4 males poles</i>
 4 244	Intercontec connector	<i>flying Intercontec, 4+5 males poles</i>

Adaptors

- PVC cable, shielded
- 4 x 0.5 mm²
- Nominal voltage 300 V


- Temperature : -30° à + 80° C
- External diameter : 6.3 mm
- Color : grey

<u>Article</u>	<u>Description</u>	
 2 137	DIN adaptor for <ul style="list-style-type: none"> ▪ <i>converter connector</i> ▪ <i>spindle connector</i> 	MS-FC <i>flying Intercontec, 4+5 males poles</i> <i>flying DIN , 4 females poles</i>
 2 136	Intercontec adaptor for <ul style="list-style-type: none"> ▪ <i>converter connector</i> ▪ <i>spindle connector</i> 	MS-FC <i>flying DIN , 4 males poles</i> <i>flying Intercontec, 4+5 females poles</i>

Extension cables

- PUR cable, shielded
- 4 x 0.75 mm² + 5 x 0.25 mm²
- Nominal voltage 30 – 300 V

- Temperature : -30° à + 80° C
- External diameter : 9.8 mm
- Color : orange

<u>Article</u>	<u>Description</u>	
 3 919	Extension flying-chassis cable for <ul style="list-style-type: none"> ▪ <i>converter connector</i> ▪ <i>spindle connector</i> 	MS-FC <i>flying Intercontec, 4+5 males poles</i> <i>Intercontec chassis, 4+5 females poles, capot</i>
3 923	▪ <i>length</i>	<i>0.5 m</i>
2 132	▪ <i>length</i>	<i>1.5 m</i>
3 233	▪ <i>length</i>	<i>3.0 m</i>
	▪ <i>length</i>	<i>5.0 m</i>

Do not hesitate to express your interest and needs and we gladly prepare an individual offer